

# HENRY®

The Professional's Formula for Success™

## 121

# Belt & Suspenders™

For Installation of Solid Wood and Engineered Wood Flooring

**Easier Clean Up vs Moisture-cured Urethanes**

- Achieves A More Robust Hardwood Installation Than Using Fasteners Alone
- High Solids Acrylic-Urethane Formula
- Excellent Initial Grab
- Fast Strength Development
- High Ultimate Bond Strength
- Moisture & Alkali Resistant
- Anti-Microbial Adhesive Protection



Tech support: 800.232.4832  
[www.wwhenry.com](http://www.wwhenry.com)

#### USE FOR:

Solid Wood and Engineered Wood flooring. HENRY® BELT & SUSPENDERS ADHESIVE is intended for use solely in conjunction with properly installed mechanical fasteners. Always follow wood flooring manufacturer's requirements for fastener type and schedule. Refer to the National Wood Flooring Association's (*NWFA*) *Installation Guidelines* for recommendations regarding the use of adhesives to increase nail holding power.

#### BONDS TO:

APA grade underlayment plywood and other flooring structures over wood, in accordance with the wood flooring manufacturer's specific recommendations for suitable substrates.

#### PREPARATION:

Substrate, adhesive and wood flooring must be acclimated at minimum 65°F (18°C) for a minimum of 48 hours before, during and after installation - subject to the flooring manufacturers recommendations. Floor must be sound, smooth, level, clean and dry. Remove dirt, wax, paint and all foreign matter that would interfere with a good bond.

#### DIRECTIONS:

Cut tip of cartridge to provide 1/8" bead. Apply adhesive sparingly to back of wood plank in an "S-shaped" pattern using a standard cartridge gun. Do not allow a heavy film to form on surface of adhesive. Flooring must be installed within 45-60 minutes, depending upon temperature and humidity.

#### CLEAN UP:

Remove wet adhesive residue with a clean, white cloth dampened with soapy water. Use mineral spirits for dried adhesive residue, carefully following warnings on the container.

#### NOTE:

**Do not reuse container.** Dispose of container and adhesive residue in accordance with federal, state and local waste disposal regulations. Do not flush adhesive down drains.  
**Freeze/thaw:** Stable to 10°F (-12°C). Avoid low temperatures or multiple freeze-thaw cycles.  
**Shelf life:** One year if not opened.  
**VOC Content:** 25 g/L; Calculated and reported, SCAQMD 1168  
**Warranty:** For complete warranty details, contact your dealer or our Customer Service Center, 800-232-4832

Made in the USA by The W. W. Henry Company,  
Aliquippa, PA 15001.

---

## HENRY Commitment

HENRY is committed to helping you get the best results in professionally installed floors. More than 75 years of experience combined with our relationships with the leading resilient, wood and carpet manufacturers ensure that you receive the products and the support you need to complete the job successfully and profitably.