

HENRY®

440

High-performance wet-set adhesive for installing rubber and vinyl cove base

Aggressive Initial Grab
Prevents slip during installation

No Open Time Required
For quicker installation

Plasticizer Migration Resistant
For installing vinyl cove base

Easy Cleanup
With water

Excellent Trowelability
Easy to use, easy to trowel

Sizes Available
11 oz., 30 oz., 1 qt., 1 gal., 4 gal.

For installation of residential or commercial rubber and vinyl cove base.
The Professional's Formula For Success.™



440 HENRY®

Cove Base Adhesive

Adhesivo para zócalos



Environmentally Compatible
Next Generation™

4 GALLONS (15,14 L.)



THE PROFESSIONAL'S FORMULA FOR SUCCESS™

HENRY® 440

HENRY 440 is The Professional's Formula For Success™ when installing rubber or vinyl cove base.

	HENRY 440	HENRY 595
COVE BASE		
Rubber Cove Base	BEST	BEST
Vinyl Cove Base	BEST	BEST



RUBBER OR VINYL COVE BASE
SAWTOOTH 1/8"D x 1/8"W x 1/8"A
310-340 lin. ft./gal. – 2 1/2" Cove Base
220-240 lin. ft./gal. – 4" Cove Base
165-180 lin. ft./gal. – 6" Cove Base

SUBSTRATES:

HENRY 440 Cove Base Adhesive may be used over:

- Structurally sound, clean, smooth, dry wall surfaces
- Abraded, glazed or metal surfaces

INSTALLATION TIPS:

- Condition the area to be installed, adhesive, and cove base to 65°F (18°C) or above for 48 hours before, during, and for 48 hours after installation.
- Walls must be smooth, sound, dry, clean and free of dirt, wax, polish, paint and all other foreign matter that may interfere with a good bond.
- Stir any liquid on the surface into the adhesive, and apply using the recommended trowel.
- Apply the adhesive to the back of the cove base or to the wall. Stay 1/8" away from the top and bottom of the cove base to prevent the adhesive from oozing.
- Place cove base into position. Butt the joints neatly.
- Using a hand roller, roll toward the previously installed section.

HENRY®

The W.W. Henry Company
400 Ardex Park Drive
Aliquippa, PA 15001
(724) 203-8000
Customer Service and Technical Information
1-800-232-4832
Visit our Web site: www.wwhenry.com

HENRY Commitment

HENRY is committed to helping you get the best results in professionally installed floors. 70 Years of experience combined with our relationships with the leading resilient, wood and carpet manufacturers ensure that you receive the products and the support you need to complete the job successfully and profitably.

HS106 (REV. B 02/07)

THE PROFESSIONAL'S FORMULA FOR SUCCESS™