

MATERIAL SAFETY DATA SHEET

HENRY[®]

972

Prepared 1/00

The W.W. Henry Company
400 Ardex Park Drive
Aliquippa, PA 15001
(724) 203-8499
Visit our Website: <http://www.wwhenry.com>

I. PRODUCT IDENTIFICATION

Name: Henry 972 Urethane Adhesive Remover
Description: Solvent based adhesive remover

II. DEPT. OF TRANSPORTATION INFORMATION

SHIPPING NAME: Not classified. HAZARD CLASS: N/A. ID#: N/A.
EMERGENCY ONLY CONTACT: CHEM-TEL-1-800-255-3924

III. HMIS (0=minimal hazard; 4 = severe hazard)

Health = 2 Flammability = 2 Reactivity = 0

IV. PRODUCT CONTENT

This product does not contain chemicals subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR 372. All components are on TSCA inventory. This product does NOT contain asbestos.

V. HAZARDOUS INGREDIENTS

INGREDIENT:

Dipropylene glycol methyl ether
CAS #34590-94-8

Propylene glycol normal butyl ether
CAS# 5131-66-8

Terpene Hydrocarbons
CAS# 5989-27-5

PERCENT:

25-30

25-30

20-30

OCCUP. EXPOS. LMT.

TLV: PEL:
100 ppm 100 ppm
STEL: STEL:
150 ppm 150 ppm
(Skin) (Skin)
N/A N/A

N/A

N/A

VI. PHYSICAL DATA

APPEARANCE: Clear, colorless. ODOR: Citrus odor. BOILING POINT: 350°F. MELTING POINT: N/A VAPOR PRESSURE (mm Hg @ 20°C): 1.0 VAPOR DENSITY: 4.1 EVAPORATION RATE: 1.0. WT/GAL (water =8.3): 7.4 lb. SOLUBILITY IN WATER: Soluble. SPECIFIC GRAVITY: 0.88 - 90.

VII. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD): 145°F (COC). FLAMMABLE RANGE: LEL: 0.6; UEL: 14. EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical, water spray. SPECIAL FIRE FIGHTING PROCEDURES: Protect fire fighters from toxic products of combustion by wearing self-contained breathing apparatus. UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers in a fire may rupture due to pressure build-up; use water to cool containers to prevent this.

VIII. HEALTH HAZARD DATA

PRIMARY ROUTE(S) OF ENTRY: Inhalation, ingestion, and direct dermal exposure. TARGET ORGANS: Upper respiratory tract, skin, eyes. EFFECTS OF OVEREXPOSURE: SKIN AND EYES: Excessive skin contact may cause drying and cracking of the skin, defatting of tissue, and result in dermatitis. Contact with eyes may cause irritation. INHALATION: May cause irritation of respiratory tract, coughing, and CNS effects such as headache, dizziness, drowsiness or nausea. CARCINOGENICITY: NTP: No; IARC Monographs: No; OSHA Regulated: No; MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Any condition generally aggravated by solvents, including preexisting upper respiratory and lung disease such as, but not limited to bronchitis, emphysema, and asthma. Existing skin conditions. FIRST AID PROCEDURES: SKIN AND EYES: Flush any eye contact with plenty of water. Additionally with skin contact, wash with soap and water. Refer to physician if irritation or symptoms persist. INHALATION: Remove to fresh air if exposed to excess concentrations of vapor. Seek medical attention if symptoms persist. INGESTION: Do not induce vomiting. Call a Poison Control Center or physician for guidance.

IX. REACTIVITY DATA

STABILITY: Stable. INCOMPATIBILITY: Strong oxidizing agents. HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, and other toxic vapors and gases that are common to thermal degradation of organic compounds. HAZARDOUS POLYMERIZATION: Will not occur.

X. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Ventilate area of spill or release. Contain spill, preventing it from entering sewer lines or waterways. Use absorbent to assist with the pick-up of material. Scrape up product and place into container. Residual of product, while still wet, can be cleaned up with warm soapy water. WASTE DISPOSAL METHOD: Dispose of container and any unused contents in accordance with Federal, State, and Local Waste Disposal Regulations. Do not flush unused contents or residue down drains. Do not reuse container

XI. SPECIAL HANDLING AND USE INFORMATION

VENTILATION: Use natural cross-ventilation, local (mechanical) pick-up, and/or general area (mechanical) ventilation to prevent an accumulation of solvent vapors, keeping in mind that the ventilation pattern must remove the heavier-than-air solvent vapors from the lower levels of the work spaces. The ventilation should be sufficient to keep the solvent vapor concentration below the TLV. RESPIRATORY PROTECTION: With adequate ventilation, respiratory equipment should not be needed. If adequate ventilation is not afforded, wear respiratory equipment approved for organic vapors. SKIN AND EYE PROTECTION: Avoid prolonged contact with skin, and contact with eyes. Wear solvent resistant gloves and spectacle-type safety glasses are recommended to prevent contact with this product.

XII. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in an area suitable for flammable mixtures. Recommended storage temperature is below 90° F. OTHER PRECAUTIONS: Vapors are flammable and are heavier-than-air. Prohibit smoking and eliminate all other sources of ignition, such as regular electrical tools and appliances, making sure that pilots on gas-fired water heaters are extinguished. WORK SITE ENVIRONMENT: Initially there may be a potential adverse impact on indoor air quality within the general work area during the installation process. Therefore you should advise the building manager or other appropriate person that: • It will be necessary to establish and maintain adequate ventilation of the work area, without causing the entry of contaminants to other parts of building; and • Persons who are sensitive to odors and/or chemicals should be advised to avoid the work area during this process.

The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

N/A - not applicable or not available
N/K - none known or not known