# **SAFETY DATA SHEET**

# SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

Product Identifier : Henry® 314 ReadySet™

Product Code : 70012322 Trade Name/Synonyms : Henry 314

Recommended Use : Premixed Mastic Adhesive.

Uses Advised Against : Use only as recommended in the product's Technical Data Sheet.

Manufacturer's name and address:

ARDEX L.P.

400 Ardex Park Drive

Aliquippa, PA 15001 USA

Information Telephone No. : (800) 232-4832 or (724) 203-8000

Website Address : <a href="http://www.wwhenry.com">http://www.wwhenry.com</a>

24 Hr Emergency Telephone # : CHEM-TEL: 1-800-255-3924 OR 1-813-248-0585 (call collect)

## **SECTION 2 – HAZARDS IDENTIFICATION**

GHS Classification per 29 CFR 1910.1200 (OSHA HCS 2012) and HPR (WHMIS 2015)

Not classified as hazardous.

**GHS Pictograms** 

None.

Signal Word

None.

**Hazard Statements** 

None.

Safe Handling Instructions: Avoid eye and skin contact. It is recommended to use safety glasses and

gloves during handling. During installation process, adequate ventilation of the work area should be maintained. Although the adhesive is low in VOC, persons who are sensitive to odors or chemicals should avoid the work area during installation. Keep container closed. Do not subject to grinding. Dispose of contents / container in accordance with federal, state, and local laws. Do not

allow product to enter drains.

During normal usage of the product as recommended, airborne dusts and mists will

not be present. See Sections 7 and 11 for further details.

**Hazards Not Otherwise Classified** 

None.

% With Unknown Acute Toxicity: Less than 1% by weight of this product is comprised of ingredients with

unknown acute toxicity

# SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS#	% (by weight)
Limestone	1317-65-3	60 – 100
Sepiolite clay	63800-37-3	0.1 – 1.0
Crystalline silica, quartz*	14808-60-7	0.1 – 1.0

\*Crystalline silica is present as an impurity from the Limestone and clay. It is not intentionally added.

Exact composition of the ingredients is claimed as a trade secret by the manufacturer.

# **SECTION 4 – FIRST AID MEASURES**

General : Call a Poison Center or doctor if you feel unwell.

**Inhalation** : Remove person to fresh air and keep at rest in a position comfortable for

breathing. Get medical attention.

**Skin contact** : Remove contaminated clothing. Flush affected skin with water. If irritation or

rash occurs, seek medical attention/advice.

**Eye contact** : Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention.

Ingestion : Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or

doctor/physician if you feel unwell.

Notes for Physician : Treat symptomatically.

#### Signs and symptoms of short-term (acute) exposure

Inhalation : May cause mild irritation of the nose, throat, mucous membranes, and respiratory

tract.

Skin : Symptoms may include mild redness or itching.

Eyes : Symptoms may include mild redness, itching, or pain.

Ingestion : Ingestion of large amounts may cause stomach irritation. May cause nausea,

vomiting, and diarrhea.

#### Effects of long-term (chronic) exposure

: Prolonged skin contact may cause skin irritations.

#### Indication of need for immediate medical attention or special treatment

: Difficulty breathing persists after removing the person to fresh air.

Any exposure to the eye which causes irritation.

### **SECTION 5 – FIRE FIGHTING MEASURES**

Suitable extinguishing media

: Carbon dioxide, dry chemical powder, alcohol-resitant foam or water spray.

Unsuitable extinguishing media

: Water jet may spread the burning material.

**Hazardous combustion products** 

: Carbon monoxide, carbon dioxide, as well as other toxic vapors and gases which

are common to thermal degradation of organic compounds.

# Special fire-fighting procedures/equipment

Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and lame. After fires have been extinguished, carefully clean all

equipment and surfaces exposed to fumes.

Environmental precautions : Do not allow material to enter drains or contaminate ground water system.

### Fire hazards/conditions of flammability

: Not flammable under normal conditions of use. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

#### Flammability classification (OSHA 29 CFR 1910.1200, WHMIS 2015)

: Not flammable.

NFPA Rating : <u>0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe</u>

Health: 0 Flammability 1 Instability 0 Special Hazards: None

# **SECTION 6 – ACCIDENTAL RELEASE MEASURES**

Personal precautions : Restrict access to area until completion of clean-up. All persons dealing with

clean-up should wear the appropriate chemically protective equipment.

Protective equipment : Refer to Section 8 for additional information on acceptable personal protective

equipment.

Emergency Procedures : This product does not contain chemicals requiring EPA notification for spills. In

case of a chemical spill, call the emergency telephone number listed in Section

1.

US CERCLA Reportable quantity (RQ): None reported.

### Methods and materials for containment and cleaning up

: Ventilate area of release. Stop spill or leak at source if safely possible. Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later disposal (see Section 13). Residual of product, while still wet, can be cleaned up with warm soapy water. Notify the appropriate authorities as required.

Prohibited materials : None known.

Environmental precautions : Do not allow product to enter drains or waterways. Do not allow material to

contaminate ground water system.

**Reference to other sections** : See Section 13 for disposal information.

# **SECTION 7 – HANDLING AND STORAGE**

Safe handling procedures : Wear suitable protective equipment during handling. (See Section 8.) Observe

good hygiene standards. Use only with adequate ventilation. Wash thoroughly after handling. Avoid contact with eyes, skin, or clothing. Sanding and grinding dusts may be harmful if inhaled. When removing this product from existing flooring (i.e. during a renovation), wear safety goggles and respiratory protection from dust due to blasting, chipping, or mechanically pulverizing. Keep container tightly closed.

**Storage requirements** : Store in a cool, dry, well-ventilated area. Store away from heat and open flame.

Avoid storing in direct sunlight. Store in original container. Keep tightly closed when

not in use. Do not reuse empty container without commercial cleaning or

reconditioning.

Incompatible materials : See Section 10.

**Special packaging materials**: Always keep in containers made of the same materials as the supply container.

# SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

Permissible Exposure Limits

: No exposure limits have been established for the product itself. Below are exposure limits for the components in the product. Since this product is a paste, airborne dust is not likely when the product is used according to the directions.

Ingredients	CAS#	ACGIH TLV		OSHA PEL	
		TWA	STEL	PEL	STEL
Limestone	1317-65-3	TLV Withdrawn In 2007	N/Av	15 mg/m <sup>3</sup> (Total dust); 5 mg/m <sup>3</sup> (respirable)	N/Av
Sepiolite clay	63800-37-3	10 mg/m <sup>3</sup> (Total dust); 5 mg/m <sup>3</sup> (respirable)	N/Av	5 mg/m <sup>3</sup> (respirable)	N/Av
Crystalline silica, quartz	14808-60-7	0.025 mg/m³ (respirable fraction)	N/Av	0.05 mg/m <sup>3</sup> (respirable) (final rule limit)	N/Av

Engineering Controls : Use general or local exhaust ventilation to maintain air concentrations below

recommended exposure limits. Ventilation should effectively remove and prevent

buildup of any vapor generated from the handling of this product.

**Personal Protection Equipment** 

**Eye / face protection**: Chemical goggles or safety glasses, as appropriate for the job.

Skin protection : Wear gloves which are impervious to the material. Materials such as nitrile rubber

or Viton (fluorocarbon rubber) are recommended.

**Body protection**: Where extensive exposure to product is possible, use resistant coveralls, apron and

boots to prevent contact.

Respiratory protection : Under normal conditions of use with adequate ventilation, respiratory protection

should not be necessary. If work process generates excessive quantities of vapor or dust, or exposures in excess of any PEL, wear an appropriate organic vapor

respirator.

Site safety equipment : An eyewash station and safety shower should be made available in the immediate

working area.

General hygiene considerations : Avoid contact with eyes, skin and clothing. Avoid breathing vapors/dust. Do not eat,

drink or smoke when using this product. Upon completion of work, wash hands thoroughly. Remove soiled clothing and wash it thoroughly before reuse. Clean all

equipment and clothing at end of each work shift.

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Paste Appearance : Off-white paste

Odor : Mild Odor threshold : N/Av pН 8.4 - 9.0Specific gravity 1.65 - 1.8**Boiling point** Coefficient of water/oil distribution : N/Av N/Av Melting/Freezing point : N/Av Solubility in water : Miscible Vapor pressure (mm Hg @ 20°C / 68°F) : N/Av Evaporation rate (n-Butyl acetate = 1) : N/Av Vapor density (Air = 1) : N/Av Volatiles (% by weight) : 20 - 30%

Volatile organic compounds (VOCs) : 7.5 g/L SCAQMD 1168

Particle size : N/Av Flammability classification : Not flammable : >93.3°C (>200°F) Lower flammable limit (% by vol) : Not available Flash point Flash point method : Setaflash closed Upper flammable limit (% by vol) : Not available Auto-ignition temperature N/Av **Decomposition temperature** : Not available : N/Av Viscosity Oxidizing properties : Not available

Explosion data: Sensitivity to mechanical impact / static discharge

: Not expected to be sensitive to mechanical impact or static discharge.

# **SECTION 10 – REACTIVITY AND STABILITY INFORMATION**

Reactivity : Not reactive.

Stability : Stable under the recommended storage and handling conditions prescribed.

**Hazardous reactions** : Hazardous polymerization does not occur.

Conditions to avoid : Extreme heat.

Materials to avoid and incompatibility

: Strong oxidizing agents; acids.

Hazardous decomposition products

: None known, refer to hazardous combustion products in Section 5.

# SECTION 11 – TOXICOLOGICAL INFORMATION

Routes of exposure : Inhalation: YES Skin Absorption: NO Skin and Eyes: Yes Ingestion: YES

Symptoms of exposure : See Section 4.

Calculated Acute Toxicity Estimates for the Product

 Inhalation
 : > 40 mg/L

 Oral
 : > 7,000 mg/kg

 Dermal
 : > 10,000 mg/kg

**Toxicological data** : See below for individual ingredient acute toxicity data.

		LC50 (4 hr)	LD50		
Ingredients	CAS No.	Inhalation, rat, mg/L	Oral, rat mg/kg	Dermal, rabbit, mg/kg	
Limestone	1317-65-3	N/Av	6,450	N/Av	
Crystalline silica, quartz	14808-60-7	N/Av	N/Av	N/Av	
Sepiolite clay	63800-37-3	N/Av	N/Av	N/Av	

**Skin corrosion or irritation** : May cause mild irritation to skin.

Serious eye damage / eye irritation : May cause mild, temporary irritation to eyes.

Respiratory or skin sensitization : None known.

Germ cell mutagenicity : None known.

Carcinogenic status : This product contains Crystalline silica. Crystalline silica (respirable size) is

classified as carcinogenic by inhalation by IARC (Group 1), ACGIH (Group A2), NTP (Group 1) and OSHA (OSHA Select carcinogen). Crystalline silica is a natural impurity in minerals such as limestone and clay. Because Crystalline silica is only carcinogenic by inhalation, this product is not considered to be a hazard. During normal usage of the product as recommended, airborne dusts will not be present. Do not sand off excess material, following initial application. When removing product from existing floors, etc. (i.e. during a renovation), do not mechanically remove under dry conditions (e.g. blasting, chipping, mechanically pulverizing).

Reproductive toxicity : None known.

Specific Target Organ Toxicity, Single Exposure

: None known.

Specific Target Organ Toxicity, Repeated Exposure

: None known.

Aspiration hazard : None known.

Additional information : N/Av

# **SECTION 12 – ECOLOGICAL INFORMATION**

Environmental effects : The product should not be allowed to enter drains or water courses, or be

deposited where it can affect ground or surface waters.

Ecotoxicity : No data available.
Biodegradability : No data available.
Bioaccumulative potential : No data available.
Mobility in soil : No data available.
PBT and vPvB assessment : No data available.
Other adverse effects : No data available.

# **SECTION 13 – DISPOSAL CONSIDERATION**

**Handling for disposal** : Handle waste according to recommendations in Section 7.

Methods of disposal : Dispose in accordance with all applicable federal, state, provincial and local

regulations. Contact your local, state, provincial or federal environmental agency

for specific rules.

Packaging : Handle contaminated packaging in the same manner as the product.

RCRA : For disposal of unused or waste material, check with local, state and federal

environmental agencies.

## **SECTION 14 – TRANSPORTATION INFORMATION**

Regulatory	UN			Packing	
Information	Number	Shipping Name	Class	Group	Label

TDG	None	This product is not regulated according to Canadian TDG regulations.	None	None	None
TDG Additional Information	None				
49 CFR/DOT	None	This product is not regulated according to US DOT regulations.	None	None	None
49 CFR/DOT Additional Information	None				

IATA : Not regulated for Air Transport
 IMDG : Not regulated for Ocean Transport
 Marine Pollutant : Not classified as a Marine Pollutant.

# **SECTION 15 – REGULATORY INFORMATION**

### Canadian Information:

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR). This SDS contains all of the information required by the HPR.

Canadian Environmental Protection Act (CEPA) information: All ingredients appear on the Domestic Substances List (DSL).

#### **US Federal Information:**

TSCA: All ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Not Hazardous.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This product is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above *de minimus* concentrations.

#### **U.S. State Right To Know Laws**

California Proposition 65: See product label for information regarding Proposition 65.

# Other State Right to Know Laws:

Present on the State RTK List?	CAS No.	CA	MA	MN	NJ	NY	PA	RI
Limestone	1317-65-3	No	YES	No	YES	No	YES	YES
Crystalline silica, quartz*	14808-60-7	No	YES	YES	YES	No	YES	YES

# **SECTION 16 – OTHER INFORMATION**

HMIS Rating : \*- Chronic Hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

Health: 0 Flammability 1 Reactivity 0 PPE: Gloves, safety glasses

Legend : ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability

Act of 1980

CFR: Code of Federal Regulations DOT: Department of Transportation DSL: Domestic Substances List EPA: Environmental Protection Agency GHS: Globally Harmonized System HPR: Hazardous Products Regulations

IARC: International Agency for Research on Cancer

Inh: Inhalation

N/Av: Not Available N/Ap: Not Applicable

NIOSH: National Institute of Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PEL: Permissible exposure limit

RCRA: Resource Conservation and Recovery Act

SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

#### Disclaimer of Liability

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

No warranty of any kind is given or implied. ARDEX L.P. will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein.

Prepared By: ARDEX L.P 400 Ardex Park Drive Aliquippa, PA, U.S.A. 15001

(724) 203-8000

Visit our Website: http://www.wwhenry.com

Revision date: : 06-Jan-2020

**End of Document**