## SAFETY DATA SHEET

### SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

### Henry<sup>®</sup> 351 Carpet Adhesive

**Product Identifier** Product ID No. Trade Name/Synonyms Material Use Uses Advised Against

Henry 351 : Adhesive for installation of Interior Carpet. :

Use only as recommended in the product's Technical Data Sheet. :

Manufacturer's name and address:



ARDEX :L.P. 400 Ardex Park Drive Aliquippa, PA 15001 USA

Information Telephone No.	: (724) 203-8000
Website Address	http://www.ardexamericas.com or http://www.wwhenry.com
24 Hr Emergency Telephone #	: CHEM-TEL: 1-800-255-3924 OR 1-813-248-0585 (call collect)

## SECTION 2 – HAZARDS IDENTIFICATION

GHS Classification per 29 CFR 1910.1200 (OSHA HCS 2012) and HPR (WHMIS 2015)

70010052

Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2B.

**GHS Pictograms** Signal Word Warning. **Hazard Statements** Causes skin irritation. Causes eye irritation. **Precautionary Statements** Wash hands and exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash before reuse. Do not subject to grinding. Dispose of contents / container in accordance with federal, state, and local laws. Do not allow product to enter drains. **Hazards Not Otherwise Classified** None % With Unknown Acute Toxicity : Up to 10% by weight of this product is comprised of ingredients with unknown acute toxicity.

## SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS #	% (by weight)
Kaolin	1332-58-7	15.00 - 40.00
Severely solvent refined heavy naphthenic petroleum distillate	64741-96-4	10.00 - 30.00

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets.

	SECTION 4 – FIRST AID MEASURES
General	: Call a Poison Center or doctor if you feel unwell.
Inhalation	: Move person to fresh air and keep at rest in a position comfortable for breathing. It breathing difficulties persist, seek immediate medical attention/advice.
Skin contact	: Remove/Take off immediately all contaminated clothing. Flush affected skin with gently flowing lukewarm water for at least 20 minutes. If rash or irritation persists, seek medical attention/advice.
Eye contact	: Immediately flush eyes thoroughly with running water for at least 20 to 30 minutes Seek immediate medical attention/advice.
Ingestion	: Never give anything by mouth to an unconscious person. Rinse mouth with water. Do NOT induce vomiting. Seek immediate medical attention/advice.
Notes for Physician	: Treat symptomatically.
Signs and symptoms of short-te	erm (acute) exposure
Inhalation	: May cause minor, temporary irritation to respiratory tract. Symptoms may include coughing and shortness of breath.
Skin	: May cause skin irritation. Symptoms may include redness and itching
Eyes	: Causes irritation to eyes. Symptoms may include redness, itching, blurred vision or pair
Ingestion	: Symptoms such as gastric pain, nausea, vomiting, and diarrhea may occur.
Effects of long-term (chronic) es	xposure
	: Prolonged inhalation may cause adverse lung effects with symptoms including coughing and shortness of breath.
Indication of need for immediate	nedical attention or special treatment
	: Difficulty breathing persists after removing the person to fresh air.
	Any exposure to the eye which causes irritation.
	Ingestion.
SE	CTION 5 – FIRE FIGHTING MEASURES
Suitable extinguishing media	: Carbon dioxide, dry chemical powder, appropriate foam or water fog.
Unsuitable extinguishing media	: water jet
Hazardous combustion products	: Carbon monoxide, carbon dioxide, and other toxic vapors and gases which are common to thermal degradation of organic compounds.
Special fire-fighting procedures/e	
	: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move container from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. After fires have been extinguished, carefully clean all

Fire hazards/conditions of flammability

**Environmental precautions** 

: Not flammable under normal conditions of use. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

: Do not allow material to enter drains or contaminate ground water system.

Flammability classification (OSHA 29 CFR 1910.1200, WHMIS 2015)

: Not flammable

## **SECTION 6 – ACCIDENTAL RELEASE MEASURES**

equipment and surfaces exposed to fumes.

Personal precautions	:	Restrict access to area until completion of clean-up. All persons dealing with clean-up should wear the appropriate chemically protective equipment.
Protective equipment	:	Refer to Section 8 for information on acceptable personal protective equipment.
Emergency Procedures	:	This product does not contain chemicals requiring EPA notification for spills. In case of a chemical spill, call the emergency telephone number listed in Section 1.
		US CERCLA Reportable quantity (RQ): None reported.
Methods and materials for contain	me	ent and cleaning up
	:	Ventilate area of release. Stop spill or leak at source if safely possible. Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later disposal (see Section 13). Residual of product, while still wet, can be cleaned up with warm soapy water. Notify the appropriate authorities as required.
Prohibited materials	:	Avoid strong oxidizing agents
Environmental precautions	:	Do not allow product to enter drains or waterways. Do not allow material to contaminate ground water system.
Reference to other sections	:	See Section 13 for disposal information.

# **SECTION 7 – HANDLING AND STORAGE**

Safe handling procedures :	Observe good hygiene standards. Use only with adequate ventilation. Do not eat, drink or smoke in the work area. Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Avoid repeated or prolonged skin contact. Avoid breathing vapors or mists of this product. Sanding and grinding dusts may be harmful if inhaled. When removing this product from existing flooring (i.e. during a renovation), wear safety goggles and respiratory protection from dust due to grinding, chipping, or shot blasting. Wear protective clothing to prevent skin contact. Promptly remove any clothing that becomes contaminated. Clean contaminated clothing before reuse. Keep container tightly closed.
Storage requirements :	Store in a cool, dry, well-ventilated area. Store away from heat and open flame. Avoid storing in direct sunlight. Store in original container. Keep tightly closed when not in use. Do not reuse empty container without commercial cleaning or reconditioning.
Incompatible materials	See Section 10.
Special packaging materials	Always keep in containers made of the same materials as the supply container.

# SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

Permissible Exposure Limits	:	No exposure limits have been established for the product itself. Below are exposure
		limits for the components in the product.

Ingredients	CAS #	ACGIH TLV		OSHA PEL	
		TWA	STEL	PEL	STEL
Kaolin	1332-58-7	2 mg/m <sup>3</sup> (respirable Dust)	N/Av	15 mg/m <sup>3</sup> (Total dust); 5 mg/m <sup>3</sup> (respirable)	N/Av
Severely solvent refined heavy naphthenic petroleum distillate	64741-96-4	5 mg/m <sup>3</sup> (as oil mist,	10 mg/m <sup>3</sup> mineral)	5 mg/m <sup>3</sup> (as oil mist, mineral)	N/Av

**Engineering Controls** 

: Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Ventilation should effectively remove and prevent buildup of any vapor or mist generated from the handling of this product.

Personal Protection Equipment	
Eye / face protection	: Safety glasses must be worn when using this product
Skin protection	: Wear chemical resistant protective clothing and impervious gloves. Materials such as nitrile rubber or Viton (fluorocarbon rubber) are recommended.
Body protection	: Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact.

Respiratory protection	: Under normal conditions of use with adequate ventilation, respiratory protection should not be necessary. If work process generates excessive quantities of vapor or dust, or exposures in excess of any PEL, wear an appropriate organic vapor respirator.
Site safety equipment	: An eyewash station and safety shower should be made available in the immediate working area.
General hygiene considerations	<ul> <li>Avoid contact with eyes, skin and clothing. Avoid breathing vapors/dust. Do not eat, drink or smoke when using this product. Clean all equipment and clothing at end of each work shift.</li> </ul>

### SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	Paste	Appearance	:	Beige, creamy paste
Odor	:	Mild	Odor threshold	:	N/Av
рН	:	9.0 – 9.5	Specific gravity	:	1.20 – 1.24
Boiling point	:	> 212°F (> 100°C)	Coefficient of water/oil distribution	:	N/Av
Melting/Freezing point	:	N/Av	Solubility in water	:	Miscible
Vapor pressure (mm Hg @ 20°C / 68°F)	:	N/Av	Evaporation rate ( <i>n</i> -Butyl acetate = 1)	:	N/Av
Vapor density (Air = 1)	:	N/Av	Volatiles (% by weight)	:	28 – 31
Volatile Organic Compounds (VOCs)	:	3.0 g/L SCAQMD	Rule 1168		
Particle size	:	N/Av	Flammability classification	:	Not flammable
Flash point	:	>212°F (100°C)	Lower flammable limit (% by vol)	:	Not available
Flash point method	:	Setaflash closed	Upper flammable limit (% by vol)	:	Not available
Auto-ignition temperature	:	N/Av	Decomposition temperature	:	Not available
Viscosity	:	Not available	Oxidizing properties	:	Not available
Evaluation datas Constitution to mas	h	niaal immaat / ata	tia diaaharwa		

Explosion data: Sensitivity to mechanical impact / static discharge

: Not expected to be sensitive to mechanical impact or static discharge.

## **SECTION 10 – REACTIVITY AND STABILITY INFORMATION**

Reactivity	Does not react.
Stability :	Stable under the recommended storage and handling conditions prescribed.
Hazardous reactions :	Hazardous polymerization does not occur.
Conditions to avoid :	High temperatures.
Materials to avoid and incompatibility	
:	Oxidizing agents.
Hazardous decomposition products	
:	None known, refer to hazardous combustion products in Section 5.

## SECTION 11 – TOXICOLOGICAL INFORMATION

Routes of exposure
Symptoms of exposure
Toxicological data

- : Inhalation: YES : See Section 4.
- : There are no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

Skin Absorption: NO Skin and Eyes: YES Ingestion: YES

	LC50 (4 hr)	LD50		
Ingredients	Inhalation, rat	Oral, rat	Dermal, rabbit	
Kaolin	N/Av	N/Av	N/Av	
Severely solvent refined heavy naphthenic petroleum distillate	N/Av	N/Av	N/Av	

Skin corrosion or irritation	May cause irritation to skin.
Serious eye damage / eye irritation	May cause irritation to eyes.
Respiratory or skin sensitization	None known.
Germ cell mutagenicity	None known.
Carcinogenic status	Not considered to be a hazard. During normal usage of the product as recommended, airborne dusts will not be present. Do not sand off excess material, following initial application. When removing adhesive from existing flooring (i.e. during a renovation), do not mechanically remove under dry conditions (e.g. grinding, chipping, shot blasting).
Reproductive toxicity	None known.
Specific Target Organ Toxicity, Single	Exposure
	Not considered to be a hazard during normal usage of the product as recommended.
Specific Target Organ Toxicity, Repea	ed Exposure
	None known.
Aspiration hazard	None known.
Additional information	N/Av

# SECTION 12 – ECOLOGICAL INFORMATION

Environmental effects	: The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.			
Ecotoxicity	: No data available.			
Biodegradability	: No data available.			
Bioaccumulative potential	: No data available.			
Mobility in soil	: No data available.			
PBT and vPvB assessment	: No data available.			
Other adverse effects	: No data available.			
SEC	SECTION 13 – DISPOSAL CONSIDERATION			
Handling for disposal	: Handle waste according to recommendations in Section 7.			

nananng ier alepeear	
Methods of disposal	: Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.
Packaging	: Handle contaminated packaging in the same manner as the product.
RCRA	: For disposal of unused or waste material, check with local, state and federal environmental agencies.

## **SECTION 14 – TRANSPORTATION INFORMATION**

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	None	This product is not regulated according to Canadian TDG regulations.	None	None	None
TDG Additional Information	None				
49 CFR/DOT	None	This product is not regulated according to US DOT regulations.	None	None	None
49 CFR/DOT Additional Information	None			•	•

: Not regulated for Air Transport

: Not regulated for Ocean Transport

### Marine Pollutant

: Not classified as a Marine Pollutant.

## SECTION 15 – REGULATORY INFORMATION

#### **Canadian Information:**

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR). This SDS contains all information required by the HPR.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on either the Domestic Substances List (DSL) or the Non- Domestic Substances List (NDSL).

#### **US Federal Information:**

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes:

Skin corrosion/irritation. Category 2

Serious eve damage/eve irritation. Category 2B.

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The threshold for this product is 10,000 pounds.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.

U.S. State Right to Know Laws

California Proposition 65: See product label for information regarding Proposition 65.

Other State Right to Know Laws: Kaolin [CAS# 1332-58-7] (MA, MN, NJ, PA, RI);

### SECTION 16 – OTHER INFORMATION HMIS Rating : \* - Chronic Hazard 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe Flammability 1 Physical Hazard 0 PPE: Gloves, safety glasses Health: 1 : ACGIH: American Conference of Governmental Industrial Hygienists Legend CAS: Chemical Abstract Services CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980 CFR: Code of Federal Regulations DOT: Department of Transportation **DSL:** Domestic Substances List EPA: Environmental Protection Agency GHS: Globally Harmonized System HPR: Hazardous Products Regulations IARC: International Agency for Research on Cancer Inh: Inhalation N/Av: Not Available N/Ap: Not Applicable NIOSH: National Institute of Occupational Safety and Health NTP: National Toxicology Program OSHA: Occupational Safety and Health Administration PEL: Permissible exposure limit RCRA: Resource Conservation and Recovery Act SARA: Superfund Amendments and Reauthorization Act STEL: Short Term Exposure Limit TDG: Canadian Transportation of Dangerous Goods Act & Regulations TLV: Threshold Limit Values TSCA: Toxic Substance Control Act TWA: Time Weighted Average

### WHMIS: Workplace Hazardous Materials Identification System

#### Disclaimer of Liability

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with any materials. It is important that the end user determines the adequacy of the safety procedures employed during the use of this product. No warranty of any kind is given or implied. ARDEX L.P. will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein.

### Prepared By:

ARDEX L.P. 400 Ardex Park Drive Aliquippa, PA, U.S.A. 15001

(724) 203-8000 Visit our Website

: http://www.ardexamericas.com or http://www.wwhenry.com

**Revision date:** 

: 10-Nov-2021

End of Document