

SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION

Product Identifiers
Product Name : **Henry® 971 EZ Plus+ Wood Adhesive**
Code No. : 1221022
Trade Name/Synonyms : Henry 971 EZ Plus+
Material Use : Moisture Cure Urethane Wood Adhesive
Restrictions on Use : Use only as recommended in the product's Technical Data Sheet

Details of the Supplier

Supplier's name and address:



ARDEX L.P.
400 Ardex Park Drive
Aliquippa, PA 15001 USA

Information Telephone No. : (724) 203-8000
Website Address : <http://www.wwhenry.com>
24 Hr Emergency Telephone # : **CHEM-TEL: 1-800-255-3924 OR 1-813-248-0585 (call collect)**

SECTION 2 – HAZARDS IDENTIFICATION

GHS Classification per 29 CFR 1910.1200 (OSHA HCS 2012) and HPR (WHMIS 2015)

Sensitization, Dermal; Category 1
Sensitization, Respiratory; Category 1
Specific target organ toxicity, single exposure; Respiratory, Category 3
Specific target organ toxicity, repeated exposure; Category 2

GHS Pictograms :



Signal Word : Danger

Hazard Statement : May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
May cause damage to lungs through prolonged inhalations or repeated exposure.

Precautionary Statements : Do not breathe vapors. Use only in a well-ventilated area. In case of inadequate ventilation wear respiratory protection. Wear protective gloves/protective clothing/eye protection. Wash hands and exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents / container in accordance with federal, state, and local laws. Do not allow product to enter drains.

Hazards Not Otherwise Specified : Contains isocyanates. Use according to the instructions. Do not heat, grind, sand, or spray this product.

% Unknown acute toxicity : 1% of this product consists of ingredients with unknown acute toxicity.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS #	% (by weight)
Distillates (petroleum), hydrotreated light	64742-47-8	5 – 10
Methylenediphenyl diisocyanate	26447-40-5	< 1
Methylenediphenyl diisocyanate (4,4'-MDI)	101-68-8	< 1

The exact percentages of the ingredients are withheld as trade secrets.

SECTION 4 – FIRST AID MEASURES

- General Information** : Call a POISON CENTER or doctor/physician if you feel unwell. Show the Safety Data Sheet to the medical personnel.
- Inhalation** : If breathing is difficult, remove person to fresh air and keep at rest in a position comfortable for breathing. Get medical attention immediately. Administer oxygen or artificial respiration as needed. Asthmatic symptoms may develop and may be immediate or delayed up to 48 hours. Extreme asthmatic reactions can be life threatening.
- Skin contact** : Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention.
- Eye contact** : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention.
- Ingestion** : Rinse mouth with water. Do NOT induce vomiting. Seek immediate medical attention/advice.
- Notes for Physician** : Treat symptomatically. Patients with respiratory exposure should be monitored up to 48 hours after exposure.

Signs and symptoms of short-term (acute) exposure

- Inhalation* : Isocyanate vapors or mist at concentrations above the TLV or PEL can irritate (burning sensation) the mucous membranes in the respiratory tract (nose, throat, lungs) causing runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function (breathing obstruction). Persons with a preexisting, nonspecific bronchial hyper-reactivity can respond to concentrations below the TLV or PEL with similar symptoms as well as asthma attack or asthma-like symptoms. Exposure well above the TLV or PEL may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in lungs). These symptoms can be delayed up to 48 hours after exposure. These effects are usually reversible.
- Skin* : Causes skin irritation with symptoms of reddening, itching, and swelling. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. Cured material is difficult to remove. Contact with MDI can cause discoloration.
- Eyes* : Causes irritation with symptoms of reddening, tearing, stinging, and swelling. May cause temporary corneal injury. Vapor or aerosol may cause irritation with symptoms of burning and tearing.
- Ingestion* : May cause irritation; Symptoms may include abdominal pain, nausea, vomiting, and diarrhea.

Effects of long-term (chronic) exposure

- : Previous repeated overexposures or a single large dose may cause certain individuals to develop sensitization to isocyanates. Those individuals may experience asthma or asthma-like symptoms as a result of later exposures to isocyanates at levels well below the TLV or PEL. These symptoms, which can include chest tightness, wheezing, cough, shortness of breath or asthmatic attack, could be immediate or delayed up to 48 hours after exposure. Extreme asthmatic reactions can be life threatening. In some cases, a sensitized individual can experience these symptoms upon exposure to dust, cold air or other irritants. This increased lung sensitivity can persist for weeks and in severe cases for several years. Sensitization can be permanent. Chronic overexposure to isocyanates has

also been reported to cause lung damage (including fibrosis and/or decrease in lung function) that may be permanent.

Prolonged contact can cause reddening, swelling, rash, and, in some cases, skin sensitization. Animal tests and other research indicate that skin contact with MDI can play a role in causing isocyanate sensitization and respiratory reaction. This data reinforces the need to prevent direct skin contact with isocyanates.

Indication of need for immediate medical attention or special treatment

- : Difficulty breathing persists after removing the person to fresh air.
- Any exposure to the skin causing a rash, swelling, itch, or pain.
- Any exposure to the eye which causes irritation.
- Ingestion.

SECTION 5 – FIRE FIGHTING MEASURES

Suitable extinguishing media : Dry chemical, carbon dioxide, foam.

Unsuitable extinguishing media : High pressure water jet may spread the fire. Isocyanates react with water to produce heat and evolve (non-flammable) gases.

Hazardous combustion products : Carbon monoxide carbon dioxide, nitrogen oxides, hydrogen cyanide, and/or low molecular weight hydrocarbons. Vapors/fumes are toxic.

Fire hazards/conditions of flammability

- : In a fire, this product will generate toxic vapors. High temperatures may cause containers to rupture.

Flammability classification (OSHA 29 CFR 1910.1200, WHMIS 2015)

- : Not classified as flammable.

Special fire-fighting procedures/equipment

- : Firefighters should wear NFPA compliant structural firefighting protective equipment, including self-contained breathing apparatus and NFPA compliant helmet, hood, boots and gloves. Avoid contact with product. Decontaminate equipment and protective clothing prior to reuse. (See Section 6 for decontamination information.) During a fire, isocyanate vapors and other irritating, highly toxic gases may be generated by thermal decomposition or combustion. Exposure to heated isocyanates can be extremely dangerous.

Environmental precautions : Do not allow product to enter waterways. Do not allow material to contaminate ground water system.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions : See Section 7 for safe handling procedures. Wear chemically resistant personal protective equipment during cleanup. Restrict access to area until completion of clean-up. All persons dealing with clean-up must be properly trained and wear the appropriate chemically protective equipment. Refer to Section 8 for additional information on acceptable personal protective equipment.

Environmental precautions : Do not allow product to enter waterways. Do not allow material to contaminate ground water system.

Spill response / clean-up : Ventilate area of release. Stop spill or leak at source if safely possible. Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Completely cover the spill area with suitable absorbent material (e.g., vermiculite, kitty litter, Oil-Dri®, etc.). Allow the absorbent material to absorb the spilled liquid. Shovel the absorbent material into an approved metal container (i.e., 55-gallon salvage drum). Do not fill the container more than 2/3 full to allow for expansion, and do not tighten the lid on the container. Repeat application of absorbent material until all liquid has been removed from the surface.

After removing spilled material as described above, decontaminate surfaces involved with the spill using a neutralization solution (mix detergent floor cleaner [if a concentrate, dilute 1 part concentrate into 9 parts water] and about 10% household

ammonia); scrubbing the surface with a broom or brush helps the decontamination solution penetrate into porous surfaces. Use caution, as the surface may be slippery. Wait at least 15 minutes after first application of the neutralization solution. Cover the area with absorbent material and shovel this into an approved metal container. Note: always wear proper PPE when cleaning up an isocyanate spill and using a neutralization solution. It may take two or more applications of the neutralization solution to decontaminate the surface. Clean up any detergent residue with fresh water.

With the lid still loosely in place, move the container holding the isocyanate waste and decontamination solution waste to an isolated, well-ventilated area to allow release of carbon dioxide. After 72 hours, seal the container, and properly dispose of the waste material in accordance with existing federal, state and local regulations.

Prohibited materials : Avoid strong oxidizing agents. Do not allow spilled material to mix with epoxy resins. Chemical reaction with epoxides causes polymerization and release of heat energy.

Special spill response procedures: If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002). Outside of the U.S. call the emergency number listed in Section 1.

US CERCLA Reportable quantity (RQ): 101-68-8 Methylene diphenyl diisocyanate (4,4'-MDI) – 5000 lbs (2273 kg).

Reference to other sections : See Section 13 for disposal information.

SECTION 7 – HANDLING AND STORAGE

Special instructions : Primary routes of exposure are by inhalation and skin contact. Do not heat or spray this material, as this will greatly increase the amount of respiratory exposure. In the case of skin contact, remove contaminated clothing immediately and wash the affected skin with soap and water.

Safe handling procedures : Do NOT breathe vapor. Do NOT swallow. Use only with adequate ventilation. Observe good hygiene standards. Do not eat, drink or smoke in the work area. Wash thoroughly after handling. Wear protective clothing to prevent skin contact. Promptly remove any clothing that becomes contaminated. Clean contaminated clothing before reuse. Keep container tightly closed.

Storage requirements : Store in a cool, dry, well-ventilated area. Store away from heat and open flame. Avoid storing in direct sunlight. Keep from freezing. Recommended storage temperature range is between 18 °C and 29 °C (65 °F and 85 °F). DO NOT EXCEED 49 °C/120 °F. Store in original container. Keep tightly closed when not in use. Do not reuse empty container without commercial cleaning or reconditioning.

Incompatible materials : See Section 10.

Special packaging materials : Always keep in containers made of the same materials as the supply container.

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

Occupational Exposure Limits	CAS No.	TLV ACGIH		PEL OSHA	
		TWA	STEL	PEL	STEL
Distillates (petroleum), hydrotreated light	64742-47-8	200 mg/m ³	ND	400 mg/m ³	ND
Methylene diphenyl diisocyanate	26447-40-5	ND	ND	ND	0,02 ppm CEIL
4,4'- Methylene diphenyl diisocyanate	101-68-8	0,005 ppm	ND	0,02 ppm	ND

Ventilation and engineering measures

: Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Ventilation should effectively remove and prevent buildup of any vapor or mist generated from the handling of this product. Under normal conditions of use, this product is not to be heated or sprayed. In cases

where the ventilation is insufficient, suitable respiratory protection equipment must be used. See "Respiratory protection" below.

Personal Protection Equipment

- Respiratory protection** : If work process generates excessive quantities of vapor, or exposures exceeding any PEL, wear a NIOSH approved organic vapor cartridge respirator.
- Eye / face protection** : Chemical goggles must be worn when using this product. A face shield is recommended if splashing is possible.
- Skin protection** : Wear chemical resistant protective clothing and impervious gloves. Materials such as nitrile rubber or Viton (fluorocarbon rubber) are recommended. It is advisable to consult with the manufacturers of gloves regarding the breakthrough time of the ingredients listed in Section 3.
- Body protection** : When prolonged exposure to the substance is possible, wear resistant overalls, aprons and boots to avoid contact.
- Other protective equipment** : An eyewash station and safety shower should be made available in the immediate working area.

General hygiene considerations : Do not breathe vapors/dust. Do not eat, drink or smoke when using this product. Clean all equipment and clothing at end of each work shift. Contaminated work clothing should not be allowed out of the workplace.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

- | | | | |
|--|--|---|-------------|
| Physical state | : paste | Appearance | : brown |
| Odor | : Faint odor | Odor threshold | : N/Av |
| pH | : N/Av | Specific gravity | : 1.39 |
| Boiling point | : N/Av | Coefficient of water/oil distribution | : N/Av |
| Melting/Freezing point | : N/Av | Solubility in water | : Insoluble |
| Vapor pressure (mm Hg @ 20°C) | : N/Av | | |
| Vapor density (Air = 1) | : N/Av | Evaporation rate (n-Butyl acetate = 1) | : N/Av |
| Volatile organic compounds (VOCs) | | | |
| | : 79 g/L SCAQMD 1168 | | |
| Volatiles (% by weight) | : 5.4% | Particle size | : N/Av |
| Flash point | : >200°F (> 93.3°C) | Lower flammable limit (% by vol) | : N/Av |
| Flash point method | : Setflash closed cup | Upper flammable limit (% by vol) | : N/Av |
| Auto-ignition temperature | : N/Av | Oxidizing properties | : None |
| Flame projection length | : N/Av | Flashback observed | : N/Av |
| Explosion data: Sensitivity to mechanical impact / static discharge | | | |
| | : Not expected to be sensitive to mechanical impact or static discharge. | | |

SECTION 10 – REACTIVITY AND STABILITY INFORMATION

- Stability and reactivity** : Stable under the recommended storage and handling conditions prescribed. The product reacts with acids, alcohols, glycols (polyols), amines. The product slowly reacts with atmospheric water vapor when used according to directions.
- Hazardous polymerization** : During uncontrolled reactions with the chemicals listed above (See Subsection "Reactivity and stability" in this Section.), this product could generate sufficient heat to burn or scald and may release toxic vapors. Only use this product according to the directions on its Technical Data Sheet.
- Conditions to avoid** : Avoid exposure to excessive heat.
- Materials to avoid and incompatibility** : Strong acids, alcohols, glycols (polyols), amines, peroxides, and other oxidizing agents.
- Hazardous decomposition products**

: Refer to hazardous combustion products in Section 5.

SECTION 11 – TOXICOLOGICAL INFORMATION

Routes of Exposure : *Inhalation*: YES *Skin Absorption*: NO *Skin and Eyes*: Yes *Ingestion*: YES

Symptoms of exposure : See Section 4.

Calculated Acute Toxicity Estimates for the Product

Inhalation : N/Av

Oral : N/Av

Dermal : N/Av

Toxicological data : See below for individual ingredient acute toxicity data.

Ingredient Name	LC50 (4 h) mg/L	LD50, mg/kg	LD50, mg/kg
	Inhalation, rat	Oral, rat	Dermal, lapin
distillat de pétrole léger hydrotraité	N. D.	> 5 000	> 2 000
diisocyanate de méthylène diphénylène (mélange d'isomères)	0,369	> 7 400	> 6 200
diisocyanate de méthylène diphénylène (4,4'-MDI)	0,178	9 200	10 000

Carcinogenic status : No components are listed as carcinogens by ACGIH, IARC, OSHA, NIOSH or NTP.

Reproductive effects : None known.

Teratogenicity : No Teratogenic effects observed. Fetotoxicity seen only with maternal toxicity.

Germ Cell Mutagenicity : None known.

Epidemiology : Not available.

Irritancy/Corrosivity : Irritating to skin and respiratory system. Seriously irritating to eyes.

Sensitization to material : Contains isocyanates, which are known to cause both respiratory and skin sensitization reactions.

Target Organ Effects, Single Exposure

: Isocyanates are known to cause respiratory irritation.

Target Organ Effects, Repeated Exposure

: Chronic overexposure to isocyanates has been reported to cause lung damage (including fibrosis and decrease in lung function) that may be permanent.

Risk of aspiration : None known.

Synergistic materials : N/Av

Other important hazards : See hazards listed in Section 2.

SECTION 12 – ECOLOGICAL INFORMATION

Environmental effects : This product should not be discharged into sewers or waterways or where it may contact soil or surface water.

Ecotoxicity : No data available.

Biodegradability : No data available.

Bioaccumulative potential: No data available.

Mobility in soil : No data available.

PBT and vPvB assessment: No data available.

Other adverse effects : No data available.

SECTION 13 – DISPOSAL CONSIDERATION

Handling for disposal : Handle waste according to recommendations in Section 7.

- Methods of disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.
- Disposal Information** : Waste must be handled in accordance with all local regulations. Do not reuse containers. Dispose of container and any unused contents in accordance with local regulations.
- RCRA** : For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14 – TRANSPORTATION INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	None	This product is not regulated according to Canadian TDG regulations.	None	None	None
TDG Additional Information	None				
49 CFR/DOT	None	This product is not regulated according to US DOT regulations.	None	None	None
49 CFR/DOT Additional Information	None				

Not regulated by IMDG.

Not regulated by IATA.

Not a Marine Pollutant.

SECTION 15 – REGULATORY INFORMATION

Canadian Information:

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR). This SDS contains all information required by the HPR.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on either the Domestic Substances List (DSL) or the Non- Domestic Substances List (NDSL).

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes:

- Skin Corrosion/Irritation; Category 2
- Sensitization, Dermal; Category 1
- Serious Eye Damage/Eye Irritation; Category 2A
- Acute Toxicity, Inhalation, Category 4
- Sensitization, Respiratory; Category 1
- Specific target organ toxicity, single exposure; Respiratory, Category 3
- Specific target organ toxicity, repeated exposure; Category 2

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The SARA 311/312 reporting threshold for this product is 10,000 pounds.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is subject to SARA 313 notification requirements, since it contains Toxic Chemical constituents above *de minimus* concentrations.

101-68-8 Methylene diphenyl diisocyanate

U.S. State Right to Know Laws

California Proposition 65: See product label for information regarding Proposition 65.

Other State Right to Know Laws:

Ingredients and State Right-to-Know Law status	N° CAS	CA	MA	MN	NJ	NY	PA	RI
Hydrotreated light petroleum distillate	64742-47-8	No	No	No	No	No	No	No
Methylene diphenyl diisocyanate (mixed isomers)	26447-40-5	No	No	No	No	No	No	No
Methylene diphenyl diisocyanate (4,4'-MDI)	101-68-8	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Soybean oil	8001-22-7	No	No	No	No	No	Yes	Yes

SECTION 16 – OTHER INFORMATION

Legend

- : ACGIH: American Conference of Governmental Industrial Hygienists
- CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CFR: Code of Federal Regulations
- DOT: Department of Transportation
- DSL: Domestic Substances List
- EPA: Environmental Protection Agency
- GHS: Globally Harmonized System
- HPR: Hazardous Products Regulations
- IARC: International Agency for Research on Cancer
- Inh: Inhalation
- N/Av: Not Available
- N/Ap: Not Applicable
- NIOSH: National Institute of Occupational Safety and Health
- NTP: National Toxicology Program
- OSHA: Occupational Safety and Health Administration
- PEL: Permissible exposure limit
- RCRA: Resource Conservation and Recovery Act
- SARA: Superfund Amendments and Reauthorization Act
- STEL: Short Term Exposure Limit
- TDG: Canadian Transportation of Dangerous Goods Act & Regulations
- TLV: Threshold Limit Values
- TSCA: Toxic Substance Control Act
- TWA: Time Weighted Average
- WHMIS: Workplace Hazardous Materials Identification System

HMIS Rating : * - Chronic Hazard 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe
*Health: *2 Flammability 1 Physical Hazard 0 PPE: Gloves, safety glasses*

NFPA Rating 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe
Health: 2 Flammability 1 Reactivity 1 Special Hazards 0

Disclaimer of Liability

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with any materials. It is important that the end user determines the adequacy of the safety procedures employed during the use of this product. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

No warranty of any kind is given or implied. ARDEX L.P. will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein.

Prepared By:
ARDEX L.P.
400 Ardex Park Drive
Aliquippa, PA, U.S.A.
15001

(724) 203-8000
Visit our Website: <http://www.wwhenry.com>

Revision date: : 02-Nov-2020

End of Document