

546

Increases applications for HENRY 545 and HENRY 547 underlayments

For recommended substrates

HENRY 545 and HENRY 547



1 GALLON (3.78 L)

LEVILING AND SKIM COATING

MORDALS THE BOND TO APPROVED SUBSTRATES MANCES FLEXISTAL STRENGTH OVER WOOD

HENRY 546 is The Professional's Formula For Success™ when used with HENRY 547.

	PRIMERS & ADDITIVES	
	HENRY 336	HENRY 546
SUBSTRATE	FLOOR PRIMER & ADDITIVE	FEATHER EDGE ADDITIVE
	As An Additive w/HENRY 331	As An Additive w/HENRY 545 & 547
Commercial Applications		OPTIONAL
Residential Applications	OPTIONAL	OPTIONAL
Patch holes and voids in wood	OPTIONAL	OPTIONAL
Skim-coat wood underlayments		REQUIRED
Underlayment joints		REQUIRED
Patch concrete on or above grade only	OPTIONAL	OPTIONAL
Patch concrete on all grade levels		OPTIONAL
Ceramic, terrazzo and marble		OPTIONAL
Polymeric poured floor		OPTIONAL
Steel		REQUIRED
Stainless Steel		REQUIRED
Lead		REQUIRED
Embossing Leveler		
Residential floor with stain-resistent wear layer		REQUIRED
Residential floor without stain-resistent wear layer		REQUIRED

INSTALLATION TIPS:

- Condition the area to be installed, adhesive, underlayment, latex, and flooring to 65°F (18°C) or above for 48 hours before, during, and for 48 hours after installation.
- Subfloor must be smooth, sound, dry, clean, and free of dirt, wax, polish, paint, and all other foreign matter which may interfere with a good bond including curing agents and sealers. Concrete must be dry and free of excess alkali.
- Mix 2 ½ parts Henry 547 to 1 part of Henry 546



The W.W. Henry Company 400 Ardex Park Drive • Aliquippa, PA 15001 (724) 203-8000 Customer Service and Technical Information 1-800-232-4832 www.wwhenry.com

HENRY Commitment
HENRY is committed to helping you get the best results in professionally installed floors. 70 Years of experience combined with our relationships with the leading resilient, wood and carpet manufacturers ensure that you receive the products and the support you need to complete the job successfully and profitably.

HS110 (REV. A 11/05)