

HENRY® 629 TileFlex Pro™ Premium Thinset Mortar

A premium, installer-grade thinset mortar used for the setting of porcelain, glass, quarry, stone, and ceramic tile.

- High bond strength and flexibility
- Sets a variety of tile types over most surfaces
- Ideal for installations over plywood or cement backer boards
- Use for exterior applications and in wet areas
- 5-hour pot life for easy installations

Applications:

HENRY 629 TileFlex Pro Premium Thinset Mortar is a Portland cement-based, polymer-modified thinset mortar used for the installation of porcelain, glass, quarry, natural stone (not moisture sensitive), and mosaic tile over most interior and exterior surfaces. It delivers high bond strength and flexibility, making it an especially good choice for exterior tile installations. For marble and other moisture-sensitive tile and stone installations, use HENRY® 316 MarbleFlex™ Marble & Stone Thinset Mortar

Bonds To:

HENRY 629 TileFlex Pro Premium Thinset Mortar bonds to concrete, cement backer boards, drywall, terrazzo, masonry, and exterior grade plywood (interiors only).

Trowel Recommendations:

Sq-Notch

¼" D x ¼" W x ¼" A

115-125 sq. ft./50 lb. bag

Sq-Notch

¼" D x 3/8" W x ¼" A

95-100 sq. ft./gal.