

# HENRY®



## FloorShield™ Floor Polish

Long-lasting, HIGH GLOSS and LOW GLOSS protection for vinyl, linoleum, and terrazzo floors.

The Professional's Formula for Success.™

**HENRY**

The flooring

FloorShield™

Low Gloss

**Floor  
Polish**

READY TO USE

Long-lasting, LOW GLOSS protection for vinyl, linoleum, and terrazzo floors

Bajo Brillo

**Pulidor para Pisos**

LISTO PARA USAR

Protección de BAJO BRILLO duradera para pisos de vinilo, linóleo y terrazo.

Use with regular or disposable mops

The Professional's Formula for Success.™

**HENRY**

The leader in flooring solutions

FloorShield™

High Gloss

**Floor  
Polish**

READY TO USE

Long-lasting, HIGH GLOSS protection for vinyl, linoleum and terrazzo floors

Alto Brillo

**Pulidor para Pisos**

LISTO PARA USAR

Protección duradera de ALTO BRILLO para pisos de vinilo, linóleo y terrazo.

Use with regular or disposable mops

1/2 Gallon  
(1.9 L)

**THE PROFESSIONAL'S FORMULA FOR SUCCESS™**

# HENRY®

## FloorShield™ Floor Polish

**Henry FloorShield™ Floor Polish is available in High Gloss and Low Gloss applications for the protection of vinyl, linoleum, and terrazzo floors.**

**Use for:** Use for polishing vinyl, linoleum, and terrazzo floors.

**Directions for Use:**

- If necessary, strip the floor with HENRY Floor Stripper and clean thoroughly using HENRY Floor Cleaner.
- If HENRY Floor Polish is being used after cleaning with HENRY Floor Cleaner, the floor surface should be rinsed with clean water.
- Soak a clean mop or polish applicator in clean water and wring out thoroughly.
- Pour approximately one quart or half the container into a clean bucket. Add more polish to bucket as needed to complete the job.
- Soak the mop or polish applicator in the polish and wring the mop out about halfway.
- Apply the polish to the floor in segments approximately 3-4 feet square. As additional coats of polish are applied to each segment, the floor should appear uniformly wet and without puddles.
- Allow each coat of polish adequate time to dry (30-60 minutes).
- After the final coat is dry to the touch, the floor can accept foot traffic. Polish requires approximately 24 hours to reach maximum toughness.

**Disposal:** Do not reuse container. Dispose of container and any contents in accordance with all regulations.

**Warranty:** For complete warranty details, contact Customer Service Center at 800-232-4832.

**⚠WARNING: EYE AND SKIN IRRITANT.** Contains Glycol Ether. Avoid contact with eyes. For eye contamination, flush well with water and call a doctor. Harmful if swallowed. Avoid getting on skin - wash thoroughly after using. Do not take internally. **KEEP OUT OF REACH OF CHILDREN.** Non-flammable.

**Freeze/Thaw:** Keep from freezing

Made in the U.S.A. for The W.W. Henry Company

Aliquippa, PA 15001

[www.wwhenry.com](http://www.wwhenry.com)

# HENRY®

The W.W. Henry Company  
400 Ardex Park Drive • Aliquippa, PA 15001  
(724) 203-8000  
Customer Service and Technical Information  
1-800-232-4832  
[www.wwhenry.com](http://www.wwhenry.com)

### HENRY Commitment

HENRY is committed to helping you get the best results in professionally installed floors. 70 Years of experience combined with our relationships with the leading resilient, wood and carpet manufacturers ensure that you receive the products and the support you need to complete the job successfully and profitably.

HS129 (REV. A 05/06)

# THE PROFESSIONAL'S FORMULA FOR SUCCESS™