SAFETY DATA SHEET

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION				
Product Identifier : Product ID No. : Trade Name/Synonyms : Material Use : Uses Advised Against : Manufacturer's name and address:	HENRY® Floor Stripper 70010692 HENRY Floor Stripper Extra-Strength Floor Cleaner and Wax Remover. Use only as recommended in the product's Technical Data Sheet. Supplier's name and address:			
ARDEX L.P. 400 Ardex Park Dr. Aliquippa, PA 15001 USA	Refer to Manufacturer			
Information Telephone No. : Website Address : 24 Hr Emergency Telephone # :	(724) 203-8000 http://www.ardexamericas.com CHEM-TEL: 1-800-255-3924 OR 1-813-248-0585 (call collect)			
SECT	ION 2 – HAZARDS IDENTIFICATION			
GHS Classification per 29 CFR 191	0.1200 (OSHA HCS 2012) and HPR (WHMIS 2015) Skin corrosion/irritation, Category 1 Serious eye damage/eye irritation, Category 1 Carcinogenicity, Category 2 Specific target organ toxicant, single exposure, Category 3, Respiratory irritation Specific target organ toxicant, repeated exposure, Category 1			
GHS Pictograms				
Signal Word	Danger.			
Hazard Statements	Causes severe skin burns and eye damage. May cause respiratory irritation. Causes damage to organs (Central Nervous System, Liver, Kidneys, and Blood) through prolonged or repeated exposure. Suspected of causing cancer.			
Precautionary Statements	Do not handle until all safety precautions have been read and understood. Do not breathe gas/mist/vapors/spray. Do not eat, drink or smoke when using this			
	product. Use only outdoors or in a well-ventilated area. Wear protective gloves			

and eye protection. Wash hands and exposed skin thoroughly after handling. Wash contaminated clothing before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents / container in accordance with federal, state, and local laws.

Hazards Not Otherwise Classified

None.

% with Unknown Acute Toxicity

4% of this product consists of ingredients with unknown acute toxicity.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS #	% (by weight)
Sodium metasilicate	6834-92-0	1.00 – 5.00
2-Butoxyethanol	111-76-2	1.00 - 5.00
Cocamide DEA	68603-42-9	1.00 - 5.00
Monoethanolamine	141-43-5	1.00 - 5.00
Diethanolamine	111-42-2	0.10 - 0.50

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets.

	SECTION 4 – FIRST AID MEASURES
General	: Call a Poison Center or doctor if you feel unwell.
nhalation	: Remove person to fresh air and keep at rest in a position comfortable for breathing. Get medical attention.
Skin contact	: Remove contaminated clothing. Flush affected skin with water. If irritation or rash occurs, seek medical attention/advice.
Eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
ngestion	 Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.
Notes for Physician	: Treat symptomatically.
Signs and symptoms of sh	ort-term (acute) exposure
Inhalation	: Symptoms may include coughing and shortness of breath.
Skin	: Symptoms may include redness and itching. Some components may be absorbed through the skin.
Eyes	: Symptoms may include redness, itching, or pain.
Ingestion	: Symptoms such as gastric pain, nausea, vomiting, and diarrhea may occur. If larg amounts are ingested, symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.
Effects of long-term (chron	ic) exposure
	 Prolonged inhalation may cause adverse lung effects with symptoms such as pulmonary edema (fluid accumulation). Repeated absorption may cause damage to central nervous system, liver, kidneys, and blood.
Indication of need for immed	liate medical attention or special treatment
	: Difficulty breathing persists after removing the person to fresh air.
	Any exposure to the eye which causes irritation or damage.
	Exposure to the skin that causes a chemical burn.
	SECTION 5 – FIRE FIGHTING MEASURES
LSuitable extinguishing media	a : Carbon dioxide, dry chemical powder, water, alcohol foam or water spray.

Suitable extinguishing media	:	Carbon dioxide, dry chemical powder, water, alcohol foam or water spray.
Unsuitable extinguishing media	:	None known.
Hazardous combustion products	:	Carbon monoxide, carbon dioxide, ammonia, nitrogen oxides (NO_x) and other toxic vapors and gases which are common to thermal degradation of organic compounds.

Special fire-fighting procedures/equipment

Incompatible materials

Special packaging materials

:	Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. After fires have been extinguished, carefully clean all equipment and surfaces exposed to fumes.			
Environmental precautions	Do not allow large quantities to enter drains.			
Fire hazards/conditions of flammability				
:	: Not flammable under normal conditions of use. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure. Ammonia gas may be liberated at high temperatures.			
Flammability classification (OSHA 29 CFR 1910.1200, WHMIS 2015)				
:	Not flammable under normal conditions of handling.			
NFPA Rating :	: 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe			
	Health: 3 Flammability 1 Instability 0 Special Hazards: None			

SECTI	ON 6 – ACCIDENTAL RELEASE MEASURES				
Personal precautions	: Corrosive! Restrict access to area until completion of clean-up. All persons dealing with clean-up should wear the appropriate chemically protective equipment.				
Protective equipment	: Refer to Section 8 for additional information on acceptable personal protective equipment.				
Emergency Procedures	: If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).				
	US CERCLA Reportable quantity (RQ): Diethanolamine: 100 lbs (45.4 kg). This is equivalent to > 20,000 lbs. (> 9090 kg) of product.				
Methods and materials for contain	nment and cleaning up				
	: Ventilate area of release. Eliminate all sources of ignition. Stop spill or leak at source if safely possible. Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later disposal (see Section 13). Residual of product, while still wet, can be cleaned up with warm soapy water. Notify the appropriate authorities as required.				
Prohibited materials	: None known.				
Environmental precautions	: Small amounts of this product may be flushed down drains, with dilution. Do not allow large amounts of this product to enter drains or waterways. Do not allow material to contaminate ground water system.				
Reference to other sections	: See Section 13 for disposal information.				
SECTION 7 – HANDLING AND STORAGE					
Safe handling procedures	: Observe good hygiene standards. Use only with adequate ventilation. Do not eat, drink or smoke in the work area. Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Avoid repeated or prolonged skin contact. Avoid breathing vapors or mists of this product. Wear protective clothing to prevent skin contact. Promptly remove any clothing that becomes contaminated. Clean contaminated clothing before reuse. Keep container tightly closed.				
Storage requirements	: Store in a cool, dry, well-ventilated area. Store away from heat and open flame. Keep tightly closed when not in use. Thoroughly rinse empty container before disposal.				

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

: Always keep in containers made of the same materials as the supply container.

: See Section 10.

HENRY[®] Floor Stripper 15-May-2019

Permissible Exposure Limits

: No exposure limits have been established for the product itself. Below are exposure limits for the components in the product.

Ingredients	CAS #	ACGIH TLV		OSHA PE	OSHA PEL	
		TWA	STEL	PEL	STEL	
Sodium metasilicate	6834-92-0	N/Av	N/Av	N/Av	N/Av	
2-Butoxyethanol	111-76-2	20 ppm	N/Av	50 ppm (skin)	N/Av	
Cocamide DEA	68603-42-9	N/Av	N/Av	N/Av	N/Av	
Diethanolamine	111-42-2	1 mg/m ³ (skin)	N/Av	3 ppm (15 mg/m ³)	N/Av	
Monoethanolamine	141-43-5	3 ppm	6 ppm	3 ppm	6 ppm	

Engineering Controls	:	Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Ventilation should effectively remove and prevent buildup of any vapor generated from the handling of this product.
Personal Protection Equipment		
Eye / face protection	:	Chemical goggles or safety glasses, as appropriate for the job.
Skin protection	:	Wear gloves which are impervious to the material. Glove materials such as nitrile rubber or Viton (fluorocarbon rubber) are recommended. Consult with glove manufacturers regarding breakthrough time for this material.
Body protection	:	Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact.
Respiratory protection	:	If work process generates excessive quantities of vapor or dust, or exposures in excess of any PEL, wear an appropriate organic vapor respirator.
Site safety equipment	:	An eyewash station and safety shower should be made available in the immediate working area.
General hygiene considerations	:	Avoid contact with eyes, skin and clothing. Avoid breathing vapors. Do not eat, drink or smoke when using this product. Upon completion of work, wash hands thoroughly. Remove soiled clothing and wash it thoroughly before reuse. Clean all equipment and clothing at end of each work shift.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	Liquid	Appearance	:	Green
Odor	:	Citrus odor	Odor threshold	:	N/Av
рН	:	12.5 – 12.9	Specific gravity	:	1.01
Boiling point	:	212°F (100°C)	Coefficient of water/oil distribution	:	N/Av
Melting/Freezing point	:	N/Av	Solubility in water	:	Soluble
Vapor pressure (mm Hg @ 20°C / 68°F)	:	N/Av	Evaporation rate (n-Butyl acetate = 1)	:	N/Av
Vapor density (Air = 1)	:	N/Av	Volatiles (% by weight)	:	96 %
Volatile organic compounds (VOCs)	:	3.9%, per CARB r	egulations		
Particle size	:	N/Av	Flammability classification	:	Not flammable
Flash point	:	>93.3°C (200°F)	Lower flammable limit (% by vol)	:	Not available
Flash point method	:	Setaflash closed	Upper flammable limit (% by vol)	:	Not available
Auto-ignition temperature	:	N/Av	Decomposition temperature	:	Not available
Viscosity	:	Not available	Oxidizing properties	:	Not available
Explosion data: Sensitivity to mechanical impact / static discharge					

: Not expected to be sensitive to mechanical impact or static discharge.

SECTION 10 – REACTIVITY AND STABILITY INFORMATION

- : Not reactive.
- Stability
- : Stable under the recommended storage and handling conditions prescribed. : Hazardous polymerization does not occur.
- Hazardous reactions Conditions to avoid
- : High temperatures.

Materials to avoid and incompatibility

Hazardous decomposition products

: Strong oxidizing agents; Acids; halogenated compounds; Alkali metals.

: None known, refer to hazardous combustion products in Section 5.

SEC	TION 11 – TOXICO	LOGICAL INFORMAT	ΓΙΟΝ
Routes of exposure	: Inhalation: YES	Skin Absorption: YES Skin a	and Eyes: Yes Ingestion: YE
Symptoms of exposure	: See Section 4.		
Acute Toxicity Estimate	properties of a mixture respective weight fra	actions of the mixture. It provid mixture itself. See 29 CRF 19	hate of the acute toxicological 50s of the ingredients and their les information when test data is 10.1200, Appendix A, paragrap
ATE Inhalation, 4 hr, rat	: > 50 mg/L		
ATE Oral, rat	: > 10,000 mg/kg		
ATE Dermal, rabbit	: > 20,000 mg/kg		
Foxicological data		ble data for the product itself, o ingredient acute toxicity data.	nly for the ingredients. See
	LC50 (4 hr)		LD50
Ingredients	Inhalation, rat, mg/L	Oral, rat, mg/kg	Dermal, rabbit, mg/kg
Sodium metasilicate	N/Av	1153	> 4640
2-Butoxyethanol	2.17	1746	N/Av
Cocamide DEA	N/Av	2700	N/Av
Diethanolamine	3.35	710	12200
Monoethanolamine	2.42	1720	1025
Respiratory or skin sensitization Germ cell mutagenicity Carcinogenic status	 None known. This product contair each classified as p these chemicals hav but sufficient eviden 	ve shown inadequate evidence	de DEA. These materials are s by IARC (Group 2B). Tests or for carcinogenicity in humans s. In a two-year study of derma
		nts are listed as carcinogens by	ACGIH, IARC, OSHA or NTP.
Reproductive toxicity	: None known.		
Specific Target Organ Toxicity, S	ingle Exposure		
	: May cause respirate	bry irritation.	
	System effects (hea absorption through	idache, dizziness, drowsiness, the skin. Due to its low concen	
Specific Target Organ Toxicity, F	Repeated Exposure		
	: Repeated exposure t	o 2-Butoxyethanol can cause live	er, kidney, and blood disorders.
Aspiration hazard	: None known.		

SECTION 12 – ECOLOGICAL INFORMATION

Environmental effects

: The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

Ecotoxicity	:	No data available.
Biodegradability	:	No data available.
Bioaccumulative potential	:	No data available.
Mobility in soil	:	No data available.
PBT and vPvB assessment	:	No data available.
Other adverse effects	:	No data available.
•	•	

SECTION 13 – DISPOSAL CONSIDERATION

U	 Handle waste according to recommendations in Section 7. Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.
00	 Handle contaminated packaging in the same manner as the product. For disposal of unused or waste material, check with local, state and federal
	environmental agencies.

SECTION 14 – TRANSPORTATION INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
49 CFR/DOT	None	Consumer Commodity	ORM-D	None	ORM-D
49 CFR/DOT Additional Information Must be a consumer-type product, in Limited Quantity size, no larger than 5.0 L per container. Package weight must not exceed 30 kg gross.					
TDG	UN1760	CORROSIVE LIQUID, N.O.S. (Sodium metasilicate; Monoethanolamine)	8	111	CORROSIVE 8
TDG Additional Information		ed under Section 1.1.7 when packages are marked "Consuin Limited Quantity size, no larger than 5.0 L per container.			

SECTION 15 – REGULATORY INFORMATION

Canadian Information:

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR). This SDS contains all of the information required by the HPR.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): Diethanolamine: 100 lbs (45.4 kg).

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: This product does not contain an Extremely Hazardous Substance under SARA Section 302.

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes:

Immediate (Acute) Health Hazard

Chronic Health Hazard.

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

HENRY[®] Floor Stripper 15-May-2019

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This product may be subject to SARA notification requirements, since it contains a Toxic Chemical constituent above its *de minimus* concentration. This product contains: diethanolamine.

U.S. State Right to Know Laws

California Proposition 65: Warning! See product label for information regarding Proposition 65.

Other State Right to Know Laws:

Ingredient on State List?	CAS NO.	CA	MA	MN	NJ	NY	PA	RI
2-Butoxyethanol	111-76-2	YES	YES	YES	YES	No	YES	YES
Cocamide DEA	68603-42-9	No	No	YES	No	No	No	No
Monoethanolamine	141-43-5	YES	YES	No	YES	No	YES	YES
Diethanolamine	111-42-2	YES	YES	No	YES	YES	YES	YES

	SECTION 16 – OTHER INFORMATION
HMIS Rating	: <u>* - Chronic Hazard 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe</u> <i>Health:</i> *3 <i>Flammability</i> 1 <i>Physical Hazard:</i> 0 PPE: Gloves, safety glasses
Legend	 ACGIH: American Conference of Governmental Industrial Hygienists CAS: Chemical Abstract Services CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980 CFR: Code of Federal Regulations DOT: Department of Transportation DSL: Domestic Substances List EPA: Environmental Protection Agency GHS: Globally Harmonized System HPR: Hazardous Products Regulations IARC: International Agency for Research on Cancer Inh: Inhalation N/Av: Not Available N/Ap: Not Available N/Ap: Not Applicable NIOSH: National Institute of Occupational Safety and Health NTP: National Institute of Occupational Safety and Health NTP: National Institute of Negram OSHA: Occupational Safety and Health Administration PEL: Permissible exposure limit RCRA: Resource Conservation and Recovery Act SARA: Superfund Amendments and Reauthorization Act STEL: Short Term Exposure Limit TDG: Canadian Transportation of Dangerous Goods Act & Regulations TLV: Threshold Limit Values TSCA: Toxic Substance Control Act TWA: Time Weighted Average WHMIS: Workplace Hazardous Materials Identification System

Disclaimer of Liability

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with any materials. It is important that the end user determines the adequacy of the safety procedures employed during the use of this product. No warranty of any kind is given or implied. ARDEX L.P. will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein.

Prepared By: ARDEX L.P. 400 Ardex Park Drive Aliquippa, PA, U.S.A. 15001 HENRY[®] Floor Stripper 15-May-2019

(724) 203-8000 Visit our Website: http://www.ardexamericas.com

Revision date:

: 15-May-2019

End of Document