

HENRY[®]

The Professional's Formula For Success[™]

248 SeamPro[™]

Carpet Seam Adhesive

For all commercial carpet backings

- **Extremely versatile: for all carpet backings including vinyl**
- **High tensile strength: seams will not pull apart**
- **Dries clear: transparent seams**
- **Easy cleanup: cleans up with water**

The W.W. Henry Company
400 Ardex Park Drive
Aliquippa, PA 15001
(724) 203-8000
1-800-232-4832
www.wwhenry.com

HENRY® 248

Carpet Seam Adhesive

Description

HENRY® 248 SeamPro is a high-strength, versatile carpet seam adhesive designed for all carpet backings, including vinyl. HENRY 248 SeamPro dries clear and cleans up easily with water.

Use For

All carpet seams.

Bonds To

Refer to the flooring manufacturer's specific recommendations for suitable substrates. HENRY 248 SeamPro Carpet Seam Adhesive bonds to all types of commercial carpet backings, including vinyl, making it an ideal choice for sealing carpet seams in residential and commercial applications.

Installation

- Remove the screw cap of the seam sealer and replace it with the nozzle applicator tip cap.
- Cut tip to allow application of a 1/8" bead.
- Apply a 1/8" continuous bead of seam adhesive to the edge of the carpet where the face yarns enter the backing.
- Apply adhesive to one edge only.
- After applying the bead, butt both edges of the carpet together while the adhesive is still wet (approximately 5-10 minutes).

Clean Up

Remove wet adhesive residue with a clean, white cloth dampened with soapy water. Use mineral spirits for dried adhesive residue. When using mineral spirits, carefully follow the recommendations of the manufacturer, and test a small area before proceeding to make sure it does not damage the surface being cleaned.

Warranty

10-Year Limited HENRY'S BEST WARRANTY. Also eligible for the ARDEX/HENRY SystemOne™ Warranty when used in conjunction with select ARDEX Engineered Cements. Failure to follow written directions will void the warranty. For complete warranty details, please contact our Customer Service Center 1-800-232-4832.

Notes

Do not reuse container. Dispose of container and adhesive residue in accordance with federal, state and local waste disposal regulations. Do not flush adhesive down drains.

- FOR PROFESSIONAL USE ONLY
- Freeze/Thaw Stable to 10°F (-12°C). Avoid low temperatures or multiple freeze/thaw cycles
- Shelf life is one year if unopened
- VOC content: 30 g/L; calculated & reported, SCAQMD 1168

Precautions

Carefully read and follow all precautions and warnings on the product label. For complete safety information, please refer to the Material Safety Data Sheet (MSDS) available at www.wwhenry.com.

Made in the USA by The W. W. Henry Company,
Aliquippa, PA 15001
© 2012 W.W. HENRY, L.P. All rights reserved.