

HENRY®

The Professional's Formula For Success™



HENRY® 256

Dual Purpose Carpet and Sheet Flooring Adhesive



Installer-grade, dual-purpose adhesive that is excellent for light to moderate traffic areas.

Use For:

Carpet backed with jute*, Action Bac®* (polypropylene), urethane foam*, latex foam (rubber)*, unitary*, unitary Action Bac®, hot melt, woven, urethane laminate and non-backed needle-punched*. Also felt-backed sheet flooring. *Extended 5-year warranty for these applications.

Key Features and Benefits:

- Aggressive early grab - helps reduce edge curl
- Short open time - for quicker installations
- Ample working time - accommodates a range of installations

Bonds To:

On all grade levels - concrete, well-bonded cementitious underlayments, APA-grade underlayment plywood (untreated), radiant-heated subfloors where temperatures do not exceed 85°F (29.4°C), terrazzo, ceramic tile, marble, certain epoxy coatings and existing, fully adhered, non-cushion backed resilient. Above grade only - well-bonded, properly primed gypsum

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)



Coverage:

Rough-Backed Carpet: V-Notch
1/8"D x 1/8"W x 1/16"A
90 - 108 sq. ft. / gal.

Smooth-Backed Carpet: V-Notch
3/32"D x 3/32"W x 3/32"A
144 - 162 sq. ft. / gal.

Felt-Backed Sheet Vinyl: Sq. Notch (Porous Surfaces)
1/16"D x 1/16"W x 1/16"A
140 - 160 sq. ft. / gal.

Felt-Backed Sheet Vinyl: U-Notch (Non-Porous Surfaces)
1/32"D x 1/16"W x 5/64"A
225 - 275 sq. ft. / gal.

HENRY®

The W.W. Henry Company
(888) 512-7339

www.wwhenry.com