

HENRY®

The Professional's Formula For Success™



HENRY® 263 WeatherPro™ Outdoor Carpet Adhesive



Use for:

Installing outdoor carpet and artificial turf. Not for use with vinyl-backed or urethane-backed carpet.

Key Features & Benefits:

- Waterproof after 2 hours
- For all weather use
- Ample working time
- Excellent initial grab reduces edge curl
- No open time required - install immediately
- Excellent long-term bond integrity
- Great for patios, boats and decks
- Outdoor use only

Bonds To:

Concrete, asphalt paving and other clean, sound, solid paving surfaces and cementitious underlayments. Untreated, exterior or marine-grade plywood decking; please note that we cannot be responsible for failures resulting from deterioration of the plywood itself. Do not install over plank decking. Substrates that have been painted, stained or otherwise coated must be tested to ensure compatibility with adhesive. Do not install over rubber or asphalt roofing.

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)

Coverage:

Smooth-Back Carpet: U-Notch
3/32"D x 1/8"W x 1/8"A
108-126 sq. ft. / gal.

Rough-Back Carpet: V-Notch
1/8"D x 1/8"D x 1/16"A

All Installations on Rough Asphalt and on Extremely Porous or Rough Concrete
70-80 sq. ft. / gal.

HENRY®

The W.W. Henry Company
(888) 512-7339

www.wwhenry.com