

HENRY®

The Professional's Formula For Success™



HENRY® 412

High-Performance Rubber Flooring Adhesive



A premium, high-strength adhesive for installing rubber sheet flooring, rubber tile and rubber and vinyl stair treads.

Use for: For installing natural and synthetic rubber sheet flooring, rubber tile, rubber stair treads and vinyl stair treads over a variety of substrates.

Key Features & Benefits:

- Superior ultimate bond-ensures long-term performance
- Outstanding dimensional stability-reduces potential for shrinkage and expansion
- Powerful initial grab-prevents slippage during installation and helps reduce edge curl

Bonds To:

Porous: Concrete, cementitious underlayments, APA grade underlayment plywood (untreated) and radiant heated subfloors where temperatures do not exceed 85°F (29.4°C) on all grade levels.

Non-porous: Staircases, terrazzo, ceramic tile, metal and certain epoxy coatings.

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)

Coverage:

Porous Substrates: Sq. Notch
1/16"D x 1/16"W x 1/16"A
99-108 sq. ft. / gal.

Non-Porous Substrates: V-Notch
1/16"D x 1/16"W x 1/16"A
108-117 sq. ft. / gal.



HENRY®

The W.W. Henry Company
(888) 512-7339

www.wwhenry.com