

# HENRY®

The Professional's Formula For Success™



## HENRY® 420

### Clear VCT (Vinyl Composition Tile) Floor Adhesive



Designed to install vinyl composition tile (VCT) in residential and commercial installations. Dries clear and has strong initial grab and ultimate bond strength.

**Use for:** Vinyl composition tile (VCT). Not for use with solid vinyl tiles and planks or other vinyl-backed floor structures.

#### Key Features & Benefits:

- Up to 18-hour working time – ideal for large commercial installations
- Moisture and alkali resistant – up 90% RH and pH of 11
- Can be used over cutback adhesive residue – reduces subfloor preparation

#### Bonds To:

**Porous:** Concrete, cementitious underlayment, APA grade underlayment plywood (untreated) and radiant heated subfloors where temperatures do not exceed 85°F (29.4°C) on all grade levels. Can also be used over properly primed gypsum underlayment (above-grade only).

**Non-porous:** Existing, well-bonded, non-cushion-backed vinyl tile and sheet flooring and existing “cutback” adhesive.

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)

#### Coverage:

**Extended Coverage:** U-Notch  
1/32”D x 1/16”W x 5/64”A  
250 - 300 sq. ft. / gal.

**Long Working time:** U-Notch  
1/16”D x 1/16”W x 3/32”A  
150 - 250 sq. ft. / gal.



# HENRY®

The W.W. Henry Company  
(888) 512-7339

[www.wwhenry.com](http://www.wwhenry.com)