

# HENRY®

The Professional's Formula For Success™



## HENRY® 452 General Purpose Epoxy Flooring Adhesive



High-strength adhesive for installing many types of flooring where wet operating conditions or heavy static or rolling loads exist.

**Use for:** Vinyl composition tile (VCT), felt-backed commercial sheet, linoleum, rubber tile, most recycled rubber, rubber and vinyl stair treads and commercial homogeneous vinyl sheet where wet operating conditions or heavy static or rolling loads are present.

### Key Features & Benefits:

- No open time-for quicker installation
- Excellent bond integrity-ensures long-term performance
- Non-flammable
- Moisture and alkali resistant
- Allows installation on all grade levels of concrete

### Bonds To:

**Porous:** Concrete, cementitious underlayments, APA grade underlayment plywood (untreated) and radiant heated subfloors where temperatures do not exceed 85°F (29.4°C) on all grade levels.

**Non-porous:** Existing resilient flooring, steel, stainless steel, aluminum, ceramic tile, terrazzo, marble and certain epoxy coatings.

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)

### Coverage:

1/32"D x 1/16"W x 5/64"A  
For all applications: U-Notch  
225 -275 sq. ft. / gal.



# HENRY®

The W.W. Henry Company  
(888) 512-7339

www.wwhenry.com