

HENRY®

The Professional's Formula For Success™



HENRY® 682 LinoLock™ Premium Linoleum Adhesive



Premium, high performance adhesive for the installation of linoleum flooring.

Use for: Commercial and residential installations of linoleum sheet and glass-backed or polyester-backed linoleum tiles.

Key Features & Benefits:

- Aggressive early grab - Ideal for all formats of linoleum flooring
- Excellent bond integrity - effectively minimizing stability and memory issues
- Moisture and alkali resistant
- Biobased carbon content (ASTM D6866)

Coverage:

U-notch

1/16" D x 1/16" W x 3/32" A
150 - 200 sq. ft. / gal.

Bonds To:

Porous: Concrete, cementitious underlayments, suspended APA grade underlayment plywood, underlayment board, and radiant heated subfloors where temperatures do not exceed 85°F (29°C) on all grade levels. Can also be used over properly primed gypsum underlayments (above grade only).

Non-porous: Terrazzo, ceramic tile, steel, stainless steel, poured polymeric floors and existing, fully adhered, non-cushion backed resilient on all grade levels.

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)

SystemOne™

GREENLINE
ENVIRONMENTAL TECHNOLOGY



HENRY®

The W.W. Henry Company
(888) 512-7339

www.wwhenry.com